

What is claimed is:

1. A dolly, comprising:  
a platform having a generally planar upper surface;  
a plurality of wheel assemblies attached to a lower surface of the platform, wherein  
5 each of the wheel assemblies includes a swivel joint and a wheel;  
a hole formed in the upper surface;  
a mounting bar extending across the hole; and  
a plurality of recesses formed in the upper surface.
- 10 2. The dolly of claim 1, further comprising:  
at least one hand-hold hole formed through the platform.
3. The dolly of claim 1, further comprising:  
a plurality of threaded mounting holes formed in the upper surface.
- 15 4. The dolly of claim 1, wherein the platform includes a plurality of side  
surfaces.
5. The dolly of claim 4, wherein the plurality of side surfaces form an octagon  
20 shape.
6. The dolly of claim 4, further comprising:  
a plurality of threaded side surface holes formed in the side surfaces.
- 25 7. The dolly of claim 1, further comprising:  
a plurality of threaded lower surface holes formed in the lower surface, wherein the  
wheel assemblies are attached to the lower surface via the threaded lower surface holes.

8. The dolly of claim 6, further comprising:  
a high hat camera mount that includes a plurality of support posts screwed into the threaded mounting holes and a support plate attached to the support posts.

5 9. The dolly of claim 1, further comprising:  
a push handle assembly attached to the platform, the push handle assembly including:  
a frame removably attached to the platform; and  
a handle member attached to the frame;  
wherein a position of the dolly is controllable by pushing on the handle member.

10

10. The dolly of claim 9, wherein the push handle assembly further includes:  
a lower support member attached to the frame; and  
an upper support member attached to the lower support via at least one lockable hinge, wherein the handle member extends from the upper support member.

15

11. The dolly of claim 10, wherein:  
the frame includes at least one plate with a plurality of mounting holes formed therein; and  
the lower support member is attached to the plate via a selected one of the mounting  
20 holes, wherein the one selected mounting hole determines an angle at which the lower support member extends from the frame.

12. The dolly of claim 9, wherein the push handle assembly further includes:  
a second platform attached to the frame, wherein the second platform is disposed  
25 adjacent to and flush with the platform.

13. The dolly of claim 9, wherein the push handle assembly further includes:  
a plurality of wheel assemblies attached to and supporting the frame.

30

14. The dolly of claim 9, wherein:  
the platform is octagonal in shape; and  
the frame includes an octagonal shaped portion dimensioned to receive the platform  
therein.

5

15. The dolly of claim 1, further comprising:  
an outrigger assembly that includes a plate attachable to the platform and a threaded  
bolt extending through a threaded hole in the plate;  
wherein a position of the dolly is fixable by rotating the bolt until the bolt engages  
10 with the ground.

16. The dolly of claim 1, further comprising:  
a fixed wheel assembly that includes a plate attachable to the platform and at least  
one wheel fixed to the plate for rotation only along one direction;  
15 wherein the one wheel confines the plurality of wheel assemblies to roll along the one  
direction.

17. A dolly, comprising:  
a platform having a generally planar upper surface, a lower surface and a plurality of  
20 side surfaces, wherein the upper and lower surfaces are octagonal in shape; and  
a plurality of wheel assemblies attached to the lower surface of the platform, wherein  
each of the wheel assemblies includes a swivel joint and a wheel;

18. The dolly of claim 17, further comprising:  
25 a plurality of threaded lower surface holes each formed in the lower surface adjacent  
one of a plurality of octagonal corners of the lower surface, wherein the wheel assemblies are  
attached to the lower surface via the threaded lower surface holes.

30

19. The dolly of claim 17, further comprising:  
a hole formed in the upper surface;  
a mounting bar extending across the hole; and  
a plurality of recesses formed in the upper surface.

5

20. The dolly of claim 19, further comprising:  
at least one hand-hold hole formed through the platform.

21. The dolly of claim 17, further comprising:  
a plurality of threaded mounting holes formed in the upper surface.

10

22. The dolly of claim 21, further comprising:  
a high hat camera mount that includes a plurality of support posts screwed into the  
threaded mounting holes and a support plate attached to the support posts.

15

23. The dolly of claim 17, further comprising:  
a plurality of threaded side surface holes formed in the side surfaces.

24. The dolly of claim 17, further comprising:  
a push handle assembly attached to the platform, the push handle assembly including:  
a frame removably attached to the platform; and  
a handle member attached to the frame;  
wherein a position of the dolly is controllable by pushing on the handle member.

20

25. The dolly of claim 24, wherein the push handle assembly further includes:  
a lower support member attached to the frame; and  
an upper support member attached to the lower support via at least one lockable  
hinge, wherein the handle member extends from the upper support member.

25

30

26. The dolly of claim 25, wherein:  
the frame includes at least one plate with a plurality of mounting holes formed therein; and  
the lower support member is attached to the plate via a selected one of the mounting  
5 holes, wherein the one selected mounting hole determines an angle at which the lower support member extends from the frame.

27. The dolly of claim 24, wherein the push handle assembly further includes:  
a second platform attached to the frame, wherein the second platform is disposed  
10 adjacent to and flush with the platform.

28. The dolly of claim 24, wherein the push handle assembly further includes:  
a plurality of wheel assemblies attached to and supporting the frame.

15 29. The dolly of claim 24, wherein:  
the frame includes an octagonal shaped portion dimensioned to receive the platform therein.

30. The dolly of claim 17, further comprising:  
20 an outrigger assembly that includes a plate attachable to the platform and a threaded bolt extending through a threaded hole in the plate;  
wherein a position of the dolly is fixable by rotating the bolt until the bolt engages with the ground.

25 31. The dolly of claim 17, further comprising:  
a fixed wheel assembly that includes a plate attachable to the platform and at least one wheel fixed to the plate for rotation only along one direction;  
wherein the one wheel confines the plurality of wheel assemblies to roll along the one  
direction.

30